

PRODUCT DATA SHEET



Avery® DOL 5900

issued: 02/04/2001

Introduction

Avery DOL 5900 is a transparent textured overlamine. It is designed to produce robust full colour graphics for short term application (maximum 2 months) on floors (indoors only). Avery DOL 5900 can be cleaned easily and has an excellent slip and wear resistance during it's functional life. It is compatible with Avery Floor Print White 60.

Description

Face-film : 100 micron, transparent matt textured vinyl overlamination film
Adhesive : permanent, clear, acrylic based
Backingpaper : one side coated bleached kraft paper, 140 g/m²

Conversion

For details of the exact working procedures, please consult Avery Technical Bulletin:

- 5.7 Recommendations for conversion, application and use of Avery Floor Marking.

Features

- Excellent wear resistance.
- Easy to handle.
- No special cleaning procedures required.
- Good adhesion.
- Excellent transparency.

Uses

Full colour graphics on indoor floors only for maximum period of 2 months.



www.averygraphics.com

Graphics Division

Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude – The Netherlands
Tel +31 71 3421500 – Fax +31 71 3421538

PRODUCT CHARACTERISTICS

Avery® DOL 5900

Physical properties

Features	Test method ¹	Results
Caliper, facefilm	ISO 534	100 micron
Caliper, facefilm + adhesive	ISO 534	135 micron
Dimensional stability	DIN 30646	0,3 mm max.
Adhesion initial	FINAT FTM-1, stainless steel	300 N/m
ultimate	FINAT FTM-1, stainless steel	500 N/m
Shelf life	Stored at 22° C/50-55 % RH	1 year
Durability*	Applied on indoor floors ONLY	2 months

Temperature range

Features	Results
Lamination temperature:	+20 - 30° C
Temperature range:	+0 °C to +40° C

Chemical properties

Features	Test method ¹	Results
Short term exposure to water, cleaning agents, IPA (Isopropylalcohol), diluted acetic acid, salt spray when used on INDOOR floors, will not damage the surface.		

Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing. All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

1) Test methods

More information about our test methods can be found on our website.

2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.



www.averygraphics.com

SYMBOL

Subotica
Tel: +381(0) 24 643100
symbol@symbol.rs

Beograd
Tel: +381(0) 11 3478262
www.symbol.rs

GRAPHIC CENTER

Zagreb
Tel: +385(0) 1 2987044

office@graphiccenter.hr
www.graphiccenter.hr