

Product Information

SOLVENT-FLOCK 5905 is a heat-sealable Viscose Flock (white, 500 μ) which is suitable for direct printing with Eco-Solvent and solvent inks.

Due to the special fiber impregnation, a photo-realistic print resolution with radiant colours is achieved.

The liner on the hotmelt side allows motifs and logos to be cut by all current CAD/CAM plotters after printing. The Flock has excellent cutting and weeding abilities and convinces due to excellent washing resistance.

SOLVENT-FLOCK 5905 is used for motifs and logos on sport, leisure and work wear.

Nylon and textiles with a hydrophobic impregnation are not suitable for heat transfer.

We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.

Standard Dimensions

500 mm x 25 m

1.000 mm x 25 m

Technical Data

Transfer Film:	Viscose Flock
Adhesive:	Copolyester-hotmelt
Thickness [mm]:	0,50 +/- 5 %
Liner:	Silicone-Paper, white

Transfer Conditions

Temperature:	155° - 170° C
Pressure:	3,5 bar [medium pressure]
Time:	17 – 20 sec.

Wash Resistance

Wash resistance:	40° C Only colour detergent. Not suitable for dry-cleaning. Wash textiles inside out.
-------------------------	--

Safety Datasheet

MSDS have not been prepared for these products, they are not subject to the MSDS requirements of the Occupational Safety and Health Administrations Hazard Communication Standard, 29 C.F.R.1910.1200 (b)(6)(v). When used under reasonable conditions and in accordance with the Poli-Tape directions for use, these products do not present a health and safety hazard. However, use or processing of the products in a manner which is not in accordance with the directions for use may affect their performance and present potential health and safety hazards.

19/02/2010